



guttering and pipe work

Shopping List

- | | |
|---|--|
| <input type="checkbox"/> Little Gem H/D Cage Frame | <input type="checkbox"/> Rokset Wire Brush |
| <input type="checkbox"/> Little Gem Extension Pole | <input type="checkbox"/> Little Gem Dust Masks |
| <input type="checkbox"/> Little Gem Roller Tray | <input type="checkbox"/> Little Gem Disposable Gloves |
| <input type="checkbox"/> Pro Mini Fabric Roller
Complete 110mm | <input type="checkbox"/> Little Gem Coveralls |
| <input type="checkbox"/> Pro Pipe Roller 90mm | <input type="checkbox"/> Little Gem Sugar Soap |
| <input type="checkbox"/> Pro Pipe Roller Replacement 2pk | <input type="checkbox"/> Little Gem Cover Quick |
| <input type="checkbox"/> Little Gem Opal Wall Brushes | <input type="checkbox"/> Rokset Wooden or Plastic Paint Stirrer |
| <input type="checkbox"/> Gap Filler | <input type="checkbox"/> Little Gem Cleaning Cloths |
| <input type="checkbox"/> Little Gem Plastic Filling Blades | <input type="checkbox"/> Rokset Canvas or Plastic Drop Sheet |
| <input type="checkbox"/> Little Gem GP Sponge | <input type="checkbox"/> Rokset Tack Cloth or Pocket Duster |
| <input type="checkbox"/> Flexisand Sanding Sponge | <input type="checkbox"/> See the Painters Checklist for a comprehensive list of
products that you may require to complete your project. |

Preparation

Galvanized gutters and downspouts must be prepared correctly to prevent rust.

- Replace damaged gutters and pipe work before paint application. Ensure all gutters and pipe work are securely fastened to the home.
- Fill any holes or cracks with the appropriate filler and allow to cure as per instructions. If using a silicone sealant ensure it is suitable to paint over.
- Sand surfaces smooth to remove old paint and sharp edges and to smooth fillers. Use a wire brush followed by a light sanding with a sanding block. (NB: sanding dust from all surface types can be harmful. Use dust masks, gloves and coveralls to protect yourself and your clothing).
- Thoroughly wash and degrease surfaces using sugar soap. Allow to dry completely before painting. If necessary, use a moss and mould cleaner prior to painting.
- Tape up adjoining surfaces and around any fixtures or fittings.
- Rinse rollers and brushes in solvent or water, dependant on the paint type. Allow to dry before use.
- Immediately before painting use a tack cloth or pocket duster to remove excess dust and fine particles.

Application - continued on next page

*This fact sheet is intended as a guide only. Rokset does not warrant the accuracy of this information.
For professional advice on your particular task, please speak to a paint specialist.
Closely follow the instructions on the paint can.*



guttering and pipe work

Application

- Paint drying times vary depending on temperature. Consult your paint professional for advice on ideal painting conditions.
- Always take the necessary safety precautions when painting. Remember ladder safety and keep the floor clear to avoid accidents.
- Speak to your paint specialist about applying a base coat, primer or rust resistant application. Priming is especially important on surfaces that have never been painted.
- Start at the top and work your way down. This allows drips to be painted over. If you are painting the whole house, paint the gutters after the fascia board and under the eaves. Then paint the walls, windows and doors followed by the downpipes.
- When painting guttering, paint the inside first followed by gutter exterior. Using a brush apply paint from side to side in long smooth strokes and finish coating the area as directed in Painting with Brushes.
- Use a pipe roller when painting pipe work. A painter's mitt can also be used to apply paint to pipe work and reach tricky spots.
- Do not use large brushes on pipe work as bristles will divide down the middle making paint application uneven and ruining the brush.
- Repeat process for each coat. The number of coats required will depend on the paint, surface and application method used. Follow instructions on the paint can regarding drying times.

Clean up and Care

See Brush and Roller Care and Cleaning for full cleaning and product care instructions.

*This fact sheet is intended as a guide only. Rokset does not warrant the accuracy of this information.
For professional advice on your particular task, please speak to a paint specialist.
Closely follow the instructions on the paint can.*